


Biorefinery approach to the extraction of bioactive compounds from Brewer's Spent Grain (BGS)

Patricia Alonso-Riaño, Rodrigo Melgosa, María Teresa Sanz, Óscar Benito-Román, Sagrario Beltrán




University of Burgos, Department of Biotechnology and Food Science. Chemical Engineering Division
Pza. Misael Bañuelos s/n 09001 Burgos (Spain). beltran@ubu.es

Flow diagram for integral Brewer's Spent Grain (BSG) valorization




Supercritical CO₂ extraction of BSG. Extraction curves and modelling



Continuous lines represent the fitting of Sovová's Model

Characterization of scCO₂ extracted BSG oil



Functional quality of scCO₂ extracted BGS oil

SFE Temperature (°C)	40 °C			60			80		
SFE Pressure (MPa)	20	30	40	20	30	40	20	30	40
PUFA/SFA*	2.04	2.22	2.08	2.22	2.11	2.04	2.03	2.00	1.99
H/H*	2.81	3.13	2.87	3.07	2.92	2.82	2.81	2.76	2.77
AI*	0.35	0.31	0.34	0.32	0.34	0.35	0.35	0.36	0.36
TI*	0.55	0.49	0.54	0.51	0.53	0.55	0.56	0.56	0.56

* PUFA/SFA: Ratio of polyunsaturated/saturated fatty acids. H/H: Hypocholesterolemic/hypercholesterolemic Index. AI: Atherogenicity index. TI: Thrombogenicity index

Acknowledgements

- To JCyL and ERDF for financial support of project BU301P18
- To Hiperbaric, S.A. for financial support of Project BIOLIGNO
- To JCyL and ESF for E. Trigueros predoctoral contract and for the contracts of P. Alonso-Riaño, Sarai del Rio Melgosa and Maria Berzal Lorenzo through the YEI program